

Operation and Safety Guide

Manual Cleat Nailer

Model 45R

Vendor Website: www.powernail.com/homedepot/

Support Phone No. 800-323-1653



WARNING

Tool Application: Installation of hardwood flooring using a 16 gage L-shaped cleat fastener

SAFETY TOPICS:



Read and understand all safety instructions and tool labels before operating.

Please visit www.powernail.com

Tool Operation:

Step	Action
1	Make sure flooring strips are together tightly
2	Place nailer on tongued edge of flooring
3	Strike plunger firmly with the rubber end of the mallet
4	Ratchet Assisted: If the plunger does not return completely, do not move the gun, the nail has not been set and you must strike the plunger again to set the nail correctly

SAFETY CHECKLIST:



1. Operators and others in work area **MUST** wear EYE and EAR protection. Use safety glasses with side shields.



2. Only use rubber end of mallet to strike the plunger

Loading/Unloading Tool:

Step	Action
1	Loading: Remove spring from feeder channel
2	Remove the feeder channel
3	Place one clip of nails into the nail channel feed slot at rear of nailer
4	Slide in the feeder channel behind the nails and attach the spring
5	Unloading: Remove the spring from the feeder channel
6	Remove the feeder channel and tilt the nailer back until the nails slide out the rear of the nailer



Model 45R in use.



Loading



Unloading